

RUNDSCHLINGEN VERSTÄRKTE AUSFÜHRUNG

Polyester- Rundschlingen mit Einfachmantel; (nach EN 1492-2)
in verstärkter Ausführung und dadurch erhöhter Tragfähigkeit



Nutzlänge in Meter	Umf.Länge in Meter	12ton	15ton	20ton	25ton	30ton	40ton	50ton	60ton
2,00	4,00	RSX0120-2000	RSX0150-2000	RSX0200-2000	RSX0250-2000	RSX0300-2000	RSX0400-2000	RSX0500-2000	RSX0600-2000
2,50	5,00	RSX0120-2500	RSX0150-2500	RSX0200-2500	RSX0250-2500	RSX0300-2500	RSX0400-2500	RSX0500-2500	RSX0600-2500
3,00	6,00	RSX0120-3000	RSX0150-3000	RSX0200-3000	RSX0250-3000	RSX0300-3000	RSX0400-3000	RSX0500-3000	RSX0600-3000
3,50	7,00	RSX0120-3500	RSX0150-3500	RSX0200-3500	RSX0250-3500	RSX0300-3500	RSX0400-3500	RSX0500-3500	RSX0600-3500
4,00	8,00	RSX0120-4000	RSX0150-4000	RSX0200-4000	RSX0250-4000	RSX0300-4000	RSX0400-4000	RSX0500-4000	RSX0600-4000
5,00	10,00	RSX0120-5000	RSX0150-5000	RSX0200-5000	RSX0250-5000	RSX0300-5000	RSX0400-5000	RSX0500-5000	RSX0600-5000
6,00	12,00	RSX0120-6000	RSX0150-6000	RSX0200-6000	RSX0250-6000	RSX0300-6000	RSX0400-6000	RSX0500-6000	RSX0600-6000
7,00	14,00	RSX0120-7000	RSX0150-7000	RSX0200-7000	RSX0250-7000	RSX0300-7000	RSX0400-7000	RSX0500-7000	RSX0600-7000
8,00	16,00	RSX0120-8000	RSX0150-8000	RSX0200-8000	RSX0250-8000	RSX0300-8000	RSX0400-8000	RSX0500-8000	RSX0600-8000
9,00	18,00	RSX0120-9000	RSX0150-9000	RSX0200-9000	RSX0250-9000	RSX0300-9000	RSX0400-9000	RSX0500-9000	RSX0600-9000
10,00	20,00	RSX0120-10000	RSX0150-10000	RSX0200-10000	RSX0250-10000	RSX0300-10000	RSX0400-10000	RSX0500-10000	RSX0600-10000
11,00	22,00	RSX0120-11000	RSX0150-11000	RSX0200-11000	RSX020-11000	RSX0300-11000	RSX0400-11000	RSX0500-11000	RSX0600-11000
12,00	24,00	RSX0120-12000	RSX0150-12000	RSX0200-12000	RSX0250-12000	RSX0300-12000	RSX0400-12000	RSX0500-12000	RSX0600-12000
13,00	26,00	RSX0120-13000	RSX0150-13000	RSX0200-13000	RSX0250-13000	RSX0300-13000	RSX0400-13000	RSX0500-13000	RSX0600-13000
14,00	28,00	RSX0120-14000	RSX0150-14000	RSX0200-14000	RSX0250-14000	RSX0300-14000	RSX0400-14000	RSX0500-14000	RSX0600-14000

Auch in anderen Größen erhältlich!